

f.o.t. catalyst

COMBUSTION CATALYST FOR DIESEL ENGINES AND BOILERS

CONTACT US / CONTATTI

Technical Support / Supporto Tecnico
technical@blutec.info

Orders – Enquiries / Ordini – Richieste di Offerta
blutec@blutec.info

Ph. +39 010 25 18 563

INSTRUCTIONS

F.O.T. CATALYST is applied as follows:

- Preferably introduced in the tanks before bunkering.
- By injection in the engine feed line, through a metering pump (dosing unit/pump available).

1 liter of F.O.T. CATALYST every 4 tons of bunker is the suggested ratio.

DESCRIPTION

Liquid containing combustion catalysts, solvents and surface-active elements.

APPLICATIONS

In slow diesel engines burning heavy fuel and medium power diesel engines burning marine diesel oil or intermediate fuel.

ADVANTAGES

- The catalysts contained in the product improve combustion.
- Breaks the emulsion and helps separate bunker and water in fuel-oil separators.
- Prevents carbon deposits in the injector nozzles.
- Reduces carbon deposits on the piston rings, discharge valves and cleaning lights.
- Extends periods between injection system overhauling.
- Reduces sulphur compounds.
- Reduces SO₃ formation due to minor catalytic action of vanadium and sodium deposits versus SO₂.

Consult our technical Service for recommendations on dosage rate based on specific problems and requirements on board.

PRECAUTIONS

Avoid contact with skin or clothes.
In case of contact with the eyes, rinse thoroughly with fresh running water.

PACKAGING

Non returnable
- Container 25 liters
- Container 208 liters